NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

MSC INTERNAL NOTE NO. 69-FM-147

June 13, 1969

Technical Library, Bellonmin Ing.

APOLLO 9 RTACF POSTMISSION REPORT



Flight Analysis Branch

MISSION PLANNING AND ANALYSIS DIVISION



MANNED SPACECRAFT CENTER HOUSTON, TEXAS

(NASA-TM-X-69649)APOLLO 9 RTACF POSTMISSION REPORT (NASA) 18 p

N74-70515

Unclas 00/99 16261

MSC INTERNAL NOTE NO. 69-FM-147

PROJECT APOLLO

APOLLO 9 RTACE POSTMISSION REPORT

By Stanley D. Holzaepfel Flight Analysis Branch

June 13, 1969

MISSION PLANNING AND ANALYSIS DIVISION NATIONAL AERONAUTICS AND SPACE ADMINISTRATION MANNED SPACECRAFT CENTER HOUSTON, TEXAS

Approved:

Charlie C. Allen, Chief

Flight Analysis Branch

Approved:

n P. Mayer, Chief

Mission Planning and Analysis Division

TABLES

Table		Page
I	RTACF COMPUTATION SUMMARY	4
II	TYPICAL RTACF SUPPORT TEAM	9
III	RTACF INHOUSE SIMULATIONS CONDUCTED	9
IV	RTACF FLIGHT CONTROL SIMULATION PARTICIPATION AND MANPOWER EXPENDED	
	(a) Participation	10 12
V	RTACF MANPOWER REQUIRED FOR MISSION SUPPORT	
	(a) SSR staff	13 13
VI	TOTAL RTACF MANPOWER REQUIRED FOR APOLLO 9 SUPPORT (ACR AND SSR)	14

APOLLO 9 RTACF POSTMISSION REPORT

By Stanley D. Holzaepfel

SUMMARY

The purpose of this document is to present a summary of the support provided by the Real-Time Auxiliary Computing Facility for the Apollo 9 mission. It does not present all of the computational capability possessed by the RTACF for support of the Apollo 9 mission, but only that which was actually requested and used. A complete list of requirements is given in references 1 through 10. A detailed description of the RTACF programs and processors is given in the Apollo 9 Flight Annex(ref. 11).

INTRODUCTION

In preparation for the Apollo 9 mission, a series of flight control simulations and inhouse simulations were supported by the RTACF. RTACF support of flight control simulations began on September 19, 1968, and ended on February 28, 1969. A total of 32 simulations were supported, in addition to 15 inhouse simulations and 24-hour support of the 241-hour Apollo 9 mission from March 3, 1969, to March 13, 1969. This document summarizes the RTACF support for both the simulations and the mission, including the manpower expended.

NOMENCLATURE

ACQ	acquisition of signal
ACR	Auxiliary Computing Room
AGOP	Apollo generalized optics processor
AGS	abort guidance system
ARS	Apollo reentry simulation
ARRS	Apollo real-time rendezvous support

CG center of gravity

CLA contingency landing area

CSM command and service modules

CM command module

DAP digital autopilot

DPS descent propulsion system

EVA extravehicular activity

FDO Flight Dynamics Officer

LGC lunar module guidance computer

LM lunar module

LOS loss of signal

LOX liquid oxygen

MPAD Mission Planning and Analysis Division

MRS mass properties, reaction control system, service propulsion system

PAO Public Affairs Officer

PFAO Postflight Auxiliary Observer

RCS reaction control system

RTACF Real-Time Auxiliary Computing Facility

RTCC Real-Time Computer Complex

SC spacecraft

SLA spacecraft/LM adapter

SM service module

SPAN Solar Particle Alert Network

SSR Flight Dynamics Staff Support room

ΔV delta velocity

DISCUSSION

Included in this document are the following topics: (a) a description of the computations made, (b) typical RTACF support team, (c) simulations supported and conducted, (d) mission manpower summary, and (e) total Apollo 9 manpower required.

A description of the computations requested, the requestor, and number of times requested are presented in table I. A typical support team of both SSR and ACR personnel for either a simulation or for mission support is shown in table II. The number of inhouse simulations conducted and manpower expended are shown in table III; while the kind, duration, personnel, and manpower expended for flight control simulations are described in table IV. The RTACF manpower required for the Apollo 9 mission in both the SSR and ACR is presented in table V. In conclusion, a summation of the manpower for all simulations and mission support is given in table VI. Total manpower expended for the Apollo 9 simulations and mission totaled 9246 manhours of work.

TABLE I.- RTACF COMPUTATION SUMMARY

The following list presents the types of computations made by the RTACF during the Apollo 9 mission and a brief description of each. This summary does not reflect all of the requirements which were levied on the RTACF. There were some programs which were not used to a great extent because of the success of the flight (i.e., LM systems programs, etc.).

Type of computation	Times	requ es ted	Requestor
Mass properties Mass properties computations include the following.		66 10	Retrofire Officer Trajectory Sup- port Chief
a. Weight-c.g. tables - used by the RTACF and RTCC trajectory processors to compute pitch and yaw trim angles b. Entry aerodynamics - used in the RTACF and RTCC entry processors c. DAP load			por onzor
AGOP AGOP computations include the following.		2 25 3	Guidance Officer Flight Plan Support Trajectory Sup-
a. Star sighting table - computes sighting, attitude, and sextant data to view a target b. Landmark sighting - computes SC attitude to view a ground target c. Optical support table - computes IMU alinement by computing star sighting angles d. Antenna pointing - computes pitch and yaw angles to point specified antenna at target site	;		port Chief
PVT The PVT processor determines the amount of SM RCS propellant remaining and how much is usable.		1	CSM propulsion
ARRS The ARRS is a generalized rendezvous program that consists of the		125	Flight Dynamics Officer
following.		20	Trajectory Sup- port Chief
a. General purpose maneuver proces- sor computes impulsive maneuver at a		75	Rendezvous Sup- port
point to achieve desired conditions		55 10	Maneuver Support MPAD

TABLE I.- RTACF COMPUTATION SUMMARY - Continued

Type of computation	Times	requested	Requestor
b. Two-impulsive and terminal phase processor - computes two impulsive maneuvers by specifying point and final conditions c. Mission plan table processor - computes finite burn to achieve a given orbit d. Relative print routine - computes relative quantities between two vehicles e. Tracking routine - computes tracking station coverage during a given period of time			
Supercritical helium Supercritical helium computations are used to monitor the LM DPS supercritical helium propellant tank pressurization system.		3	LM propulsion
Lift-off REFSMMAT The lift-off REFSMMAT computation gives the onboard REFSMMAT used until the IMU is realined in orbit.		1	Trajectory Sup- port Chief
Checkout monitor. The checkout monitor is a table that displays orbital parameters at a specified time.	:	47	Trajectory Sup- port Chief a. NORAD b. Smithsonian c. Satellite sighting
PFAO The PFAO computation consists of various trajectory parameters used for real-time reports to NASA Headquarters and postflight reports.		48	Postflight personnel
PAO. The PAO computation consists of data for SC signting from various cities, press releases, and news conferences.		7	Public Affairs Office
FDO orbit digitals. The FDO orbit digitals provide orbital parameters based on current orbit or projected orbit.		7	Trajectory Sup- port Chief

TABLE I.- RTACF COMPUTATION SUMMARY - Continued

Type of computation	Times requested	Requestor
Sun look angles. The sun look angles computation provides the angles the sun vector makes with respect to the SC coordinate system	20	Flight plan sup- port personnel
Navigation update. The navigation update computation provides a state vector in the correct units to update the S-IVB, CSM, LGC, or AGS computers.	5 · 2	Guidance officer Trajectory Sup- port Chief
Groundtracks and plot tape.— The groun tracks and plot tape provide a time hi tory of SC position in either computer output or X-Y plot tape.		Trajectory Sup- port Chief a. Earth Re- sources Division b. Recovery c. Operations Applications Office
Maneuver evaluation.— The maneuver evaluation computes an equivalent maneuver from a preburn and postburn vector.	4	Flight Dynamics Officer Trajectory Sup- port Chief
CSM MRS The CSM MRS computes a complete RCS propellant budget based on the current flight plan.	10	CSM propulsion
Work schedule processor. The work schedule processor computations in-	2	Frajectory Sup- port Chief
clude the following.	30	Flight plan sup- port
 a. Radar ACQ and LOS data b. SC daylight/darkness data c. Moon rise/moon set data d. Orbital events e. Landmark sighting f. Star ACQ and LOS data 	6 10	Retrofire Officer Track

g. Closest approach data h. Pointing data

TABLE I.- RTACF COMPUTATION SUMMARY - Continued

Type of computation	Times requested	Requestor
Entry groundtracks.— The entry ground- track computation provides a time history of SC position during entry.		Trajectory Support Chief a. Retrofire Officer b. Recovery c. Track
Maneuver confirmation The maneuver confirmation computes actual maneuvers		Trajectory Support Chief
by application of ΔV residuals from a particular maneuver to the nominal	1	Flight Dynamics Officer
ΔV targets.	2	Retrofire Officer
Radiation dosage. The radiation dosage processor provides a time history of radiation dose and dose rate for both CSM and LM cabins.	12	Radiation
Docking alinement. The docking alinement computes REFSMMAT or attitude of CSM or LM in docked configuration.	3	Guidance Officer
LM and CSM SEENA. The LM and CSM SEENA programs compute electrical	2	LM electrical power systems
capability, energy drain, and energy remaining for any configuration.	1	CSM electrical power systems
CM and SM pointing. The CM and SM pointing data provide time time history data from radar sites to track the entering vehicle.	17 6	Track MPAD
EVA attitude control.— The EVA attitude control provides REFSMMAT and gimbal angles for optimum lighting for extravehicular activity.	1	Flight plan support
K-factor. The K-factor processor determines the atmospheric density	18	Flight Dynamics Officer
multiplier for optimum near-earth orbital propagation.	5	Trajectory Support Chief
<u></u>	2	MPAD

TABLE I.- RTACF COMPUTATION SUMMARY - Concluded

Type of computation	Times requested	Requestor
Lifetime The lifetime processor determines the orbital lifetime of a particular vehicle.	5	MPAD Flight Dynamics Officer
Command load. The command load provides conversions of engineering unit with the proper scaling factor to uplink octal units.		Trajectory Sup- port Chief
Sun impingement processor.— The sun impingement processor determines gimbal angles to point a specific location on the SC toward the sun.	1	Guidance Officer
SPAN The SPAN processor determines the radiation intensity that results from solar flares.	1	Radiation
Wind data. The wind data processor predicts mode I impact points based on the current wind profile at launch pad.	19	Recovery
Entry. The entry computations include the following. a. CLA/ARS - determination of deorbit burn or entry or both to hit a specified target b. Apogee - SM RCS burn about apogee and resultant impact point c. Hybrid - combination of an	173 25 50	Retrofire Officer Deorbit support Trajectory Sup- port Chief
SM RCS and a CM RCS burn to hit a target. d. No SLA separation - a deorbit that uses an S-IVB LOX dump and CM RCS burn e. Block data - a set of deorbit times and events sent to the crew		

for emergency use

TABLE II.- TYPICAL RTACF SUPPORT TEAM [SIMULATION OR MISSION]

SSR staff	
Trajectory Support Chief 1	
Assistant Trajectory Support Chief 1	
Specialist (maneuver, rendezvous, deorbit)	
Nontechnical support 1	
ACR staff	
ACR Chief 1	
Trajectory Analyst 3	
Program Consultant 2	
Nontechnical support 4	
Total	5
TABLE III RTACF INHOUSE SIMULATIONS CONDUCT	ED
Number of simulations 1	5
Total simulation hours 69	9
Average technical personnel 10	C
Average nontechnical personnel	4
Total manpower, hr 966	5

TABLE IV.- RTACF FLIGHT CONTROL SIMULATION

PARTICIPATION AND MANPOWER EXPENDED

(a) Participation

Type	Date month-day	Duration, hr	SSR	ACR
ME 103	9-19-68	13	2	9
ME 103	9-20-68	12	2	12
ME 103	9-21-68	12	2	9
FMES	.11-1-68	10.5	3	9
FMES	11-2-68	11	3	10
TD&E	1-8-69	6	3	7
REND	1-9-69	12	4	12
REND	1-10-69	10.5	3	13
REND	1-11-69	10.5	4	12
SPS	1-13-69	15.5	14	10
REND	1-14-69	10.5	3	13
ENTRY	1-15-69	11.5	6	9
REND	1-24-69	. 10.5	3	10
LM EVAL	1-27-69	12	3	3
DPS-1	1-28-69	10.5	<u>)</u>	8
SPS-5	1-20-09	10.7	4	O
REENTRY	1-29-69	12.5	6	9
DPS-1	1-30-69	10.5	5	8
REND	2-3-69	10.5	5	11
S-N-S	2-4-69	10	3	8

TABLE IV.- RTACF FLIGHT CONTROL SIMULATION

PARTICIPATION AND MANPOWER EXPENDED - Continued

(a) Participation

Туре	Date month-day	Duration, hr.	SSR	ACR
DPS-1	2 -6- 69	11	4	9
TD&E	2-7-69	8.	3	7
EVA	2-8-69	<u>1</u> 41	2	3
REND	2 -11- 69	12	3	12
REND	2-12-69	11	4	10
DPS-1	2-13-69	10	14	8
REND	2-14-69	10.5	3	10
EVA	2-15-69	6	2	3
L.A.	2-20-69	6 . 5.	2	8
REND	2-21-69	12	5	12
N.S.	2-22-69	4.5.	3	12
ENTRY	2-24-69	12	5	10
DPS-1	2-28-69	12	14	10

TABLE IV.- RTACF FLIGHT CONTROL SIMULATION PARTICIPATION AND MANPOWER EXPENDED - Concluded

(b) Manpower

Summary		ACR
Number of simulations	32	32
Average length, hr	10.2	10.2
Average technical personnel per simulation	Ъ,	5
Average nontechnical personnel per simulation	1	14
Manpower expended for simulations, man hours	2938	1632
Total manpower, man hours	457	70

TABLE V.- RTACF MANPOWER REQUIRED FOR MISSION SUPPORT

Position	Number of personnel	Hours present	Total manhours			
(a) SSR staff						
Trajectory Support Chief, FAB	1	246	246			
Asst. Trajectory Support Chief, FAB	1.	246	246			
Maneuver specialist, OMAB	2	137	274			
Deorbit specialist, LAB	2	84	168			
Rendezvous specialist, OMAB	2	35	70			
Nontechnical personnel, ITT	1	246	246			
(b) ACR staff						
ACR Chief, TRW	1	246	246			
Trajectory analyst, TRW and MPAD	3	246	738			
Program consultant, TRW and LEC	2	246	492			
Nontechnical support, ITT and LEC	14	246	984			
Total 3710						

TABLE VI.- TOTAL RTACF MANPOWER REQUIRED FOR APOLLO 9 SUPPORT (ACR AND SSR)

Total inhouse simulation support (ACR), manhours	966
Total flight control simulation support (ACR), manhours	1632
Total flight control simulation support (SSR), manhours	2938
Total mission support for ACR, manhours	2460
Total mission support for SSR, manhours	1250
Total manpower expended, manhours	9246

REFERENCES

- 1. Kranz, Eugene F.: RTACF Real Time Computing Requirements for AS-503/103/LM-3-Mission D. MSC memo, June 28, 1968.
- 2. Kranz, Eugene F.: Revision A to RTACF Requirements for AS-503/103/LM-3-Mission D. MSC memo, July 10, 1968.
- 3. Kranz, Eugene F.: Revision B to RTACF Requirements for Mission D. MSC memo, January 15, 1969.
- 4. Kranz, Eugene F.: Revision C to the RTACF Requirements for Mission D. MSC memo, January 29, 1969.
- 5. Piland, Robert O.: Apollo 9 Real-time Auxiliary Computer Facility (RTACF) Requirement. MSC memo, January 20, 1969.
- 6. Hage, George H.: Real Time Orbital Elements for the CSM on the Apollo 9 Mission. NASA memo, February 26, 1969.
- 7. Kranz, Eugene F.: Request for Service-RTACF. MSC memo, January 31, 1969.
- 8. Lacy, W. R.: SSR/RTACF Trajectory Support for Apollo Mission D. MSC memo 69-FM13-2, January 7, 1969.
- 9. Chilton, Robert G.: Generation of Information for Mission Support Model. MSC memo, February 27, 1969.
- 10. Tilderman, Herbert A.: Apollo 9 Orbital Trajectory and Plotting Data. MSC memo, February 25, 1969.
- 11. Flight Analysis Branch: Operational Support Plan for the Real Time Auxiliary Computing Facility Apollo 9 Flight Annex. MSC IN 69-FM-49, February 17, 1969.